

Product Data Sheet

Collection: **Alpin**
 Product: **LARCH Country**
 Product Code: **LCEB**

TECHNICAL PRODUCT DESCRIPTION:

Branches	are permitted
Cracks	putty filled cracks are permitted
Cotter	permitted
resin	putty filled pitch pockets are permitted
Worm	not permitted
Discolourisation	permitted
Grain	permitted
Color difference	is a characteristic of natural wood

WOOD TYPE:

Larch - The Larch is an extremely hard-wearing softwood. The lively surface optic gives every room an unmistakable note full of character.

WOOD TREATMENT:

untreated - The planks have not received a thermo treatment (Vulcano). The wood is obtained from carefully managed forests managed within Central Europe. The mafi philosophy ensures the complete tree is used and nothing is wasted. The resulting variations in lengths and width underline the character of a natural wooden floor.

AVAILABLE DIMENSIONS:

2480 x 190/220 x 16

2480 x 190/220 x 21

Natural wooden floors made in AUSTRIA

mafi Natural Wooden Floors GmbH

Utzweihstrasse 21+25 · A 5212 Schneegattern +43 · [0]7746 2711 - 0 · f: +43 [0]7746 3747 · office@mafi.com · www.mafi.com

mafi
· walk on art

SURFACE:

The surface finishing of mafi natural wooden flooring is done exclusively with natural oils, which cure oxidatively. These oils consist of naturally renewable raw materials and are 100% biodegradable. Natural oils are harmless and generally antiallergenic. They provide a pleasant surface and a natural optical appearance of wood.

To obtain the desired visual appearance and quality, each mafi natural wooden floor is oiled twice. This is the reason why we distinguish between:

- **Production surface** = professionally preoiled surface ex works
- **Installed surface** = professionally re-oiled surface after the flooring is laid.

Exception: All floors of the Domino collection are delivered with a raw surface.

There are some defined criteria from mafi for the installed surface. These should be completed by the certified partners of mafi to ensure a guarantee.

AVAILABLE SURFACE TREATMENT:

brushed / natural oil: By brushing wood, it gets a characteristic surface structure depending on its naturally grown wood grain. natural oiled - the natural oil intensifies the colour and grain of the wood.

brushed / white oil: By brushing wood, it gets a characteristic surface structure depending on its naturally grown wood grain. white oiled - white pigments in the oil brighten the floor.

brushed / natural oil / lye treated: By brushing wood, it gets a characteristic surface structure depending on its naturally grown wood grain. natural oiled - the natural oil intensifies the colour and grain of the wood.

brushed / white oil / lye treated: By brushing wood, it gets a characteristic surface structure depending on its naturally grown wood grain. white oiled - white pigments in the oil brighten the floor.

UNDERFLOOR HEATING:

Nearly all mafi natural wooden floors are suitable for underfloor heating systems. Only exceptions are Larch Country, Larch Country Vulcano and Vulcano Rosso). Please have a look into the [installation instructions](#) for detailed information. With a room temperature of 21°C the floor's surface temperature should be maximum 27°C.

ADHESIVE (PVA):

mafi natural wooden floors are exclusively glued together with casein adhesive. It is manufactured with water, carbon, lime, acetic acid and without any use of formaldehyde and solvents. PVA, the principal component for casein adhesive is used for packaging food and therefore it is free of any poisonous category.

MOISTURE CONTENT OF THE WOOD:

The moisture content of mafi natural wooden floors is between 6 – 8 % ex works. (exception: all Vulcano floors are between 2 – 5 %). This is guaranteed through special analyzers which are continuously calibrated.

TONGUE AND GROOVE:

The width of each tongue and groove is circa 4mm. It is about keyway. Tongue and groove is on all sides for easy installation.

Exception: All floors of the Domino collection are delivered glued on a net without tongue and groove.

INSTALLATION:

mafi natural wooden floors can be installed floatingly, with floor joists or by gluing. Please take the [mafi installation instructions](#) into consideration.

USAGE:

All mafi natural wood floors comply with CE directives in accordance with **ÖNORM EN 14342**.

P1 / P2 / O: P1 Suitable for low and medium traffic: bedroom, children's room, lounge, etc. P2 Suitable for medium traffic and heavily frequented areas: kitchen, dining-room etc. O Suitable for commercially used zones. Attention! Only after consultation with an expert and compliance test of the actual area!

IMPORTANT ADVICE:

mafi natural wood floors are pure natural products and therefore unique. Differences in color and textures are because of different growing conditions of the single tree. Samples and exhibition spaces can never match the delivered floor to 100%.

Natural wooden floors made in AUSTRIA

mafi Natural Wooden Floors GmbH

Utzweihstrasse 21+25 · A 5212 Schneegattern +43 · [0]7746 2711 - 0 · f: +43 [0]7746 3747 · office@mafi.com · www.mafi.com

DUE DILIGENCE:

The subsurface as well as the goods for installation has to be checked if the standards are kept to the following:

- Parquet works DIN 18356;
- Wooden floors: DIN EN 13489;
- Tolerances in building construction DIN 18202;

Each plank has to be checked regarding proper quality prior to installation.

The completion of a heating protocol is imperative if an installation on underfloor heating is realized.

TECHNICAL DATA:

Density:	0,44 - 0,85 g/cm³	g/cm ³
Thermal resistance:	0,09 - 0,19 m²*K/W	m ² k/w
Hardness (Brinell scale)	19 N/mm²	N/mm ²
Lindane and Pentachlorophenol	< 5 ppm	ppm
Fire certification	CFL-s1	
Emission Category	E1	

DISCLAIMER:

With publication of this product data sheets all previous versions invalid. Errors, prices, and technical modifications are possible to change without notice.