




Wide Plank



Herringbone



Chevron

Woodos Solid Oak flooring boards are made from highest quality European Oak or French Oak. Woodos can supply the boards unfinished or the boards can be pre-finished to the specified colour and texture which produces an exceptional finish, bringing a luxurious feel to any project. The perfect choice for anything for easy open living to a long lasting commercial application.

PRODUCT DETAILS

PRODUCT CODE	WSOF WSOE
FINISH	Unfinished or Prefinished
PRICE	-\$-\$\$\$
PRODUCT COLLECTION	Woodos
WEB CATEGORY	Flooring
CONSTRUCTION	Solid Oak
SPECIES	French Oak or European Oak
GRADE	Character + Clear
PATTERN	Plank + Herringbone + Chevron
SURFACE	Lightly Brushed
PROFILE	Tongue & Groove
MICRO BEVEL ON LONG SIDES	Micro bevel 4 sides
TOP LAYER	Solid
BACK LAYER	N/A
ADHESIVE	N/A
THICKNESS	9mm to 18mm
PLANK WIDTHS	90mm to 280mm
PLANK LENGTHS	1000mm - 4000mm
HERRINGBONE DIMENSIONS	350x70mm 600x120mm
CHEVRON DIMENSIONS	520x70mm
INSTALL	Installation & Maintenance.pdf
RESIDENTIAL WARRANTY	25
COMMERCIAL WARRANTY	5

INSTALLATION METHODS

FULLY BONDED	Yes 6mm trowel (recommended)
NAILED	with glue nail through tongue
FLOATED ON UNDERLAY	No
OVER JOIST	Yes 18mm Planks Only @ 300mm centres
OVER UNDERFLOOR HEATING	Yes

GRADING CRITERIA

BRANCHES	Healthy knots are permitted
CRACKS	End and stress cracks up to 300mm are filled with putty
COTTER	Not permitted
WORN	Not permitted
DISCOLOURISATION	Permitted
GRAIN	Permitted
COLOR DIFFERENCE	Is a characteristic of natural wood

TECHNICAL CRITERIA

ORIGIN	Europe
RESPONSIBLE CERTIFICATION	FSC / CERT II
JANKA HARDNESS RATING	34 N/mm ²
FORMALDEHYDE EMISSION	E1
PENTACHLOROPHENOL EMISSION	< 5 ppm
SLIP TESTING	P3
FIRE CLASSIFICATION	BSEN 13238:2010
REACTION TO FIRE FLOORS (CRF)	3.8 kW/m ²
REACTION TO FIRE WALLS & CEILINGS	Group 3
THERMAL RESISTANCE	0.07 - 0.17 m ² *K/W